



COMP 2012H Honors Object-Oriented Programming and Data Structures

Self-study: C++ string class

Dr. Desmond Tsoi

Department of Computer Science & Engineering
The Hong Kong University of Science and Technology
Hong Kong SAR, China



Rm 3553, desmond@ust.hk

COMP 2012H (Fall 2021)

1 / 13

Common Public Member Functions

- `string::append`
- `string::assign`
- `string::at`
- `string::begin`
- `string::capacity`
- `string::clear`
- `string::compare`
- `string::copy`
- `string::c_str`
- `string::data`
- `string::empty`
- `string::end`
- `string::erase`
- `string::find`
- `string::find_first_not_of`
- `string::find_first_of`
- `string::find_last_not_of`
- `string::find_last_of`
- `string::insert`
- `string::length`
- `string::max_size`
- `string::operator=`
- `string::operator+=`
- `string::operator[]`
- `string::push_back`
- `string::rbegin`
- `string::rend`
- `string::replace`
- `string::resize`
- `string::find`
- `string::size`
- `string::substr`
- `string::swap`

Introduction

- **C strings** consist of a **sequence** of characters terminated by the '\0' character, and are stored as **char arrays**.
- **C string** is not a basic data type and does not natively support any operations which are, instead, provided by a set of functions defined in the **cstring** library.
- There is a **C++ string class** which allows you to manipulate **string objects** as if they are from a basic type.
 - ▶ *string construction and initialization*
 - ▶ *input and output*
 - ▶ *indexing*
 - ▶ *comparisons*
 - ▶ *substrings*
 - ▶ *swapping strings*
 - ▶ *string length*
 - ▶ *finding substrings and characters*
 - ▶ *replacing characters in string*
 - ▶ *inserting characters in string*

Rm 3553, desmond@ust.hk

COMP 2012H (Fall 2021)

2 / 13

Constructors

- Default constructor: To create an empty string.

```
string s; // s is ""
```

- To create a string from *n* copies of a character.

```
string rating(3, 'A'); // rating is "AAA"
```

- To create a string object from a C string.

```
string s1("hello");  
string s2 = "hello"; // both are "hello"
```

- To create from a substring of a C string:

```
string s("hello", 4); // s is "hell"
```

Rm 3553, desmond@ust.hk

COMP 2012H (Fall 2021)

3 / 13

Rm 3553, desmond@ust.hk

COMP 2012H (Fall 2021)

4 / 13

Assignment and Concatenation

- To assign one string object to another string object.

```
string s1("thank"), s2;           // s1 is "thank", s2 is ""
s2 = s1;                         // s2 is "thank" too
```

- To assign a C string to a string object.

```
string s; s = "good";           // s is "good"
```

- To assign a character to a string object.

```
string s; s = 'A';              // s is "A"
```

- To concatenate 2 string objects.

```
string s1("thank"), s2 = "you"; // s1 is "thank", s2 is "you"
string s3;                      // s3 is ""
s3 = s1 + " " + s2;            // s3 is "thank you"
s1 += s2;                      // s1 is "thankyou"
```

Accessing Individual Characters

- To get the number of characters in a string object.

```
string s = "hkust";
cout << s.length();                // output is 5
```

- 2 ways to get the *j*th character of a string object.

- use the subscript operator `[]` like the C strings

- $0 \leq j \leq \text{length}() - 1$
- you don't have to worry about the terminating NULL character, which will be handled by the class.
- if the index $j > \text{length}() - 1$, the behaviour is **undefined**.

- member function `at()`

- similar to `[]`, but check if the index is valid \Rightarrow **slower**.
- runtime error** if the index is **beyond** the string length.

```
string s = "hkust";
cout << s.at(1);                  // output is 'k'
s.at(9) = 'a';                   // runtime error
```

Basic I/O

- To read one word into a string object.

```
string s;
cin >> s;                        // skip leading whitespaces
```

- To output a string object to the console.

```
string s = "hkust";
cout << s;                        // output "hkust" to the screen
```

- To get one line of text until a newline or other delimiter character.

```
string s;
getline(cin, s);                  // read until a newline character
getline(cin, s, 'X');             // read until an 'X' which is not read in
                                // but discarded. Next input starts after 'X'.
```

String Comparisons

- Comparison is based on the lexicographical order.

- Comparison operators: `<`, `<=`, `>`, `>=`, `==`, `!=`

- compare()** function: `s1.compare(s2)`


- returns 0 if the strings are the same
- returns a +ve number if s1 is lexicographically greater than s2
- returns a -ve number if s1 is lexicographically smaller than s2



Substrings

- `s.substr(j, N)`: To get a copy of the substring of `s` starting at the index `j`, consisting of `N` characters.

```
// index: 01234567890123456789012345678901234567890123456789
string s = "The rain in Spain stays mainly in the plain.";
string s1 = s.substr(1, 2);
string s2 = s.substr(9, 8);
string s3 = s1 + " is " + s2;
cout << s3 << endl; // Output: he is in Spain
```



Example: Find and Replace

```
#include <iostream> /* File: sfind.cpp */
using namespace std;

int main()
{
    //index: 0123456789012345678901234567890123
    string s("The rain in Spain stays mainly in the plain.");
    cout << s.length() << endl;

    int p1 = s.find("ain"); // Find the first "ain"
    int p2 = s.find("ain", 10); // First "ain" from the 10th char
    int p3 = s.find("ain", 20); // First "ain" from the 20th char
    int p4 = s.find("ain", 30); // First "ain" from the 30th char
    int p5 = s.find("ain", 50); // First "ain" from the 50th char
    cout << p1 << ' ' << p2 << ' ' << p3 << ' ' << p4 << ' ' << p5 << endl;

    s.replace(p1, 3, "hino"); cout << s << endl;
    cout << s.find("ain", 10) << endl; // First "ain" from the 10th char again
    return 0;
}
// 44
// 5 14 25 40 -1
// The rhino in Spain stays mainly in the plain.
// 15
```

Find and Replace

- `s.find(s2, j)`: To search for the first occurrence of a substring `s2`, starting from the `j`th character of current string object `s`. It returns
 - ▶ if found, the position of the found substring in the string object.
 - ▶ otherwise, a constant `string::npos` = the max. unsigned int.
- `s.rfind(s2, j)`: similar to `find()` but search backwards.
- `s.replace(j, N, s2)`: To replace the substring of `s` that starts at the `j`th character, consisting of `N` characters by `s2`.



Example: Find and Replace ..

```
#include <iostream> /* File: find-replace.cpp */
using namespace std;

void print_words(const string word[], int num_words) {
    for (int j = 0; j < num_words; j++)
        cout << word[j] << endl;
}

int main() {
    string s1("et"); // substring to be replaced
    string s2("ad"); // replacing string
    const int num_words = 5;
    string word[num_words] = { "met", "deet", "pets", "eta", "set" };
    cout << "Before replacement" << endl; print_words(word, num_words);

    // Replace the first occurrence of "et" by "ad" in each word
    for (int j = 0; j < num_words; j++)
    {
        int index = word[j].find(s1, 0);
        word[j].replace(index, s1.length(), s2);
    }

    cout << "After replacement" << endl; print_words(word, num_words);
    return 0;
}
```

That's all!

Any questions?

